



A Furukawa Company

Your Optical Fiber Solutions Partner®

OFS | www.ofsoptics.com

Item # AC03720-10, Duplex 2.5 mm Based Construction Step-Index 200 μm HCS® Riser

OFS 2.5 mm HCS fiber cables are designed primarily for industrial data-communication applications. Taking advantage of the durability and toughness of HCS optical fibers, these tight-buffer cables surround the fiber with high-strength aramid yarn and are protected with a tough 2.5 mm diameter PVC jacket.



[Optical Properties](#) | [Cable Design](#) | [Installation and Usage Specifications](#) | [Ordering Information](#) | [Typical Applications](#) | [Crimp & Cleave Compatibility](#) | [Options](#)

Optical Properties

Type	Multimode Step-Index
Attenuation	@ 850 nm, ≤ 6 dB/km
Fiber Specifications	CF01493-10 , 200 0.37 NA Low OH Optical Fiber

Cable Design

Construction	Duplex
--------------	--------

Numerical Aperture	0.37
Fiber Core Diameter	200 ± 4 µm
Sub-Unit Diameter	2.5 ± 0.1 mm
Outer Cable Diameter	3.5 x 6.0 mm
Cable Weight	20 kg/km
Outer Jacket Material	PVC
Outer Jacket Color	Orange

Installation and Usage Specifications

Installation Load Maximum	220 lb 979 N
Minimum Bend Installation	53 mm
Operating Load Maximum	110 lb 489 N
Minimum Bend Operating	35 mm
Operating Temperature	-20 to +80 °C
Storage Temperature	-40 to 80 °C

Ordering Information

Product Description Code HCP-M0200T-A02VD

Order From Location AVON LOCATION
1.888.438.9936 toll-free in the United States and Canada
1.860.678.0371 from outside the U.S.A.
55 Darling Drive
Avon, CT 06001, USA

Order By Item # AC03720-10

Note The operating temperature ranges are general guidelines. Consult with our Technical Sales department to determine the optimal coating and jacketing material for your specific application.
1.860.678.6636

Typical Applications

Factory Automation Near-IR Spectroscopy
Industrial Communications
Laser Power Delivery

Crimp & Cleave Compatibility

SMA Connectors
ST Connectors

Options

Jacket Color
Print Legend
Terminated Assemblies