

Specifications for Plastic Optical Fiber


Multicore POF™ MCL-2000-24

Issued on : April 8, 2020

Issued by : Asahi Kasei Corporation
Plastic Optical Fiber
Marketing & Development Gr

1, STRUCTURE

ITEM	UNIT	Specifications
Core Material		PMMA
Clad Material		Fluorinated Polymer
Core reflective index		1.49
Reflective index Profile		Step index
Fiber Diameter	μm	2000 ± 120
Core Number		13000
NA		0.5
Jacket Material		PE
Jacket Diameter	μm	2400 ± 80
Jacket Color		Black
Approx. weight	g/m	5.0



2, PROPERTIES

ITEM	UNIT	Specifications	
Storage Temperature Range	°C	-55 ~ 60	
Application Temperature Range	°C	-55 ~ 60	
Tensile Strength at Break Point	N	≥ 280	*1

Though the image transmitted through 13,000-core POF may show concentrically faded areas, this does not indicate a defective product but is a characteristic of the product due to the structure of the POF.

Sample conditions

Temperature: T = 23°C
Humidity: RH = 50%
Storage time: t = 200h

*1 : Interval between grippers = 100 mm, Tensile Speed = 100mm/min

3, RoHS certification

The product does not contain RoHS 2 hazardous substances, Cadmium, Lead, Mercury, Chromium (VI), PBB, PBDE, DIBP, DEHP, DBP and BBP intentionally.